



Purex Extraction Systems for Lasers...

A must for healthy workshops

Protects lenses & components
Prevents downtime
Reduces rejects
Protects operator health
Improves engraving quality

Unique features ensure operator safety, product quality, production rates and profits remain high.

Quick Change Filters

Filters are easily changed in seconds with no mess or disruption. Returns clean, purified air to the workplace

Plug & Play

Units are plug & play and mounted on castors making them easy to manoeuvre

Comply with Regulations

Ensures compliance with all relevant international health and safety and environmental regulations.

Low Cost of Ownership

Patented filter designs deliver low cost of ownership compared to other filter extraction systems.

Easy Installation

No need to put holes in walls or roofs to vent fumes outside your building. Unobtrusive and fits into small places.

Fully Adjustable

Adjustable speed control allows the operator to achieve optimum extraction. Automatic closed loop control maintains extraction flow.

Wide Variety of Materials

Filters fume from most materials including organic, metals and plastics



FumeCube

Volts / Watts	230 V + - 10% / 0.14kW
Sound rating	60 dBA
Max flowrate	200 m ³ /hr
Cabinet height	350mm
Cabinet width (not inc. hose)	308mm
Cabinet depth (not inc. hose)	283mm
Cabinet weight inc. filters	12.5Kg
Hose recommended	51mm



UPX 325

Volts / Watts	230 V + - 10% / 0.24kW
Sound rating	45 dBA
Max flowrate	400 m ³ /hr
Cabinet height inc. castors	885mm
Cabinet width (not inc. hose)	465mm
Cabinet depth (not inc. hose)	465mm
Cabinet weight inc. filters	41Kg
Hose recommended	80mm
Controls	Illuminated ON/OFF switch, Filter Blocked LED Speed Control

UPX 425

Volts / Watts	230 V + - 10% / 0.12kW
Sound rating	52 dBA
Max flowrate	460 m ³ /hr
Cabinet height inc. castors	1070 mm
Cabinet width (not inc. hose)	455 mm
Cabinet depth (not inc. hose)	480 mm
Cabinet weight inc. filters	55 Kg
Hose connection	80mm
Controls	Fully automatic flow control plus gas and particle monitoring



UPX 850HD

Volts / Watts	230 V + - 10% / 2.4kW
Sound rating	65 dBA
Max flowrate	800 m ³ /hr
Cabinet height inc. castors	1150 mm
Cabinet width (not inc. hose)	540 mm
Cabinet depth (not inc. hose)	670 mm
Cabinet weight	80 Kg
Hose connection	100mm
Controls	Fully automatic flow control plus gas and particle monitoring



Laser & Sign Technology

109 Bonds Rd Punchbowl NSW 2196
Ph 02 9584 9499 FAX 02 9584 9550

www.lastech.com.au